



David Round, Inc.  
Ruger Division  
10200 Wellman Road  
Streetsboro, OH 44241  
Phone: 440-248-4700  
Fax: 440-248-8544  
www.rugerindustries.com

**STRONG****VERSATILE****ADJUSTABLE****AFFORDABLE**

## HP-2A

- **4000 lb. Capacity**
- **Adjustable legs-open wide for big loads**

### ACCESSORIES

- **Barrel Grip**
- **Floor Lock**
- **Extension boom**
- **Phenolic or Polyurethane wheels**
- **Power-Pak**

### STANDARD FEATURES

- Meets Ruger's engineering standards of 150% structural overload of maximum rated capacity
- Adjustable legs to straddle large oversized loads
- Double action hand pump for quicker and easier lift
- Built-in hydraulic overload relief valve (An original Ruger patent)
- Needle type release valve permits pin-point control over lowering and holding of the heaviest or lightest loads
- Steel casters with roller bearing wheels
- Swivel hook with safety latch for to support heavy loads



With the adjustable leg feature, accomodating oversized loads is easy. Tested and exceeds ANSI/ASME PALD-12C standards. Meets ANSI Z.535

Prices, Specifications, and Options are subject to Change Without Notice.

All Ruger products are shipped F.O.B. Streetsboro, Ohio 44241  
Unit Ships-NMFC #189240 - Class 85 Shipping Wt. 740 lbs

FAX: 440-248-8544

E-mail: [info@davidround.com](mailto:info@davidround.com)



David Round, Inc.  
 Ruger Division  
 32405 Aurora Road  
 Solon, OH 44139  
 Phone: 440-248-4700  
 Fax: 440-248-8544  
 www.rugerindustries.com

**STRONG**

**VERSATILE**

**ADJUSTABLE**

**AFFORDABLE**

# MODEL: HP-2A

Model .....	HP-2A
Max. Capacity .....	4000 lbs
Overall Base Length .....	76-1/2"
Overall Width .....	37"-54"-67"
Overall Height .....	84"
Width Between Legs .....	24"-40"-53"
Boom Reach Retracted .....	60"
Boom Reach Extended .....	101"
Boom Height (lowest position) .....	39 3/4"
Boom Height (highest position) .....	119 1/4"
Ext. Boom Height (lowest position) .....	12 1/2"
Ext. Boom Height (highest position) .....	146 1/2"
Height of Legs .....	8 1/4"
Wheel Diameter-Load Wheels .....	6"
Wheel Diameter-Steering Wheels .....	6"

PUMPING CYCLES needed to raise boom through full travel; 31 with crane set for speed and 170 with crane set for power.

